



Digital Indoor/Outdoor Thermometer With Cabled Probe

Product Images



Description

The digital indoor/outdoor thermometer is a sleek temperature unit, with a cabled probe.

The main unit is for indoor use, and features two individual displays – the top is for indoor temperature, and the bottom is for the reading taken from the probe. Aswell as this, the unit also stores minimum and maximum readings taken within a 24 hour time period.

The probe is on the end of a 150cm cable, this can be fed through a window or door to be used outside, as it is fully weatherproof.

Technical Specification

- Indoor Temperature Range: 0°C to 50°C
- Outdoor Temperature Range: -40°C to 70°C
- Manual Min/Max Reset
- Measurement: °C and °F
- Dimensions: L 60 x D 24 x H 83
- Battery: 2 x AAA
- Battery Life: 12-18 months
- Warranty: 1 Year
- Manufacturer: TFA

Additional Information

Brand	TFA Dostmann
Humidity	no
Temperature	yes
Temperature Sensor	no
Wet Bulb	no
Clip-On	no
Humidity Range	no
Probe Type	Cable Probe
Cable Length	1.5 Metres
Auto Switch Off	no
Hold Function	no
HACCP Compliant	no
Min/Max Readings	yes
Warranty	1 Year
Calendar	no
Calibration	Can Be Calibrated
Dew Point	no
Weatherproof	no
Water Resistant	yes
Waterproof	no
Solar Light	no
Protective Case	no
Probe Temperature	no
Handheld	no
Dual Display	yes
Cabled Probe	yes

Temperature Resolution	+/- 1°C
Humidity Sensor	no
Comfort Level Indicator	no
Moon Phase	no
Backlight	no
Indoor Temperature	yes
Indoor Humidity	no
Clock	no
Transmission Range	no
Transmission Frequency	no
Temperature Range	-40 to 70°C
Temperature Accuracy	+/- 1°C
Measuring Units	°C
Humidity Resolution	no
Humidity Accuracy	no
Power	Battery
Outdoor Temperature	no
Size : Depth	2.5cm
PC Connection	no
Touch Screen	no
Min/Max Reset	yes
Dew Point Alarm	no
High/Low Humidity Alarm	no
High/Low Temp Alarm	no
Outdoor Humidity	no
Size : Height	8.3cm
Size : Width	6cm

Data Storage

Stores Min/Max Temperatures Since Last Manual Reset

Additional Options

Temperature Calibration Certificate

2 Point Temperature Calibration (0°C / 60°C)

2 Point Temperature Calibration (please specify temperature points)

1 Point Temperature Calibration (0°C)