



# Window Thermometer With Solar Powered Light

### **Product Images**



### Description

The Solar powered Vision digital thermometer has a handy solar power panel which will illuminate the display throughout the night. This handy piece of equipment will simultaneously display external temperature along with there minimum/maximum readings for day and the current time.

There is no hassle of re setting the readings as this unit will automatically do this for you.

Simply attach to the window using the adhesive pads included.

#### **Technical Specification**

- Temperature Range: -25°C to 70°C
- Measurement: °C or °F
- Dimensions: L102 x W94 x D66mm
- Battery: 1 x AAA and 1x AAA Rechargeable (for light function)
- Warranty: 1-Year
- Manufacturer: TFA

## **Additional Information**

Brand     IPA Dostmann       Humidity     no       Temperature     yes       Temperature Sensor     no       Wet Bulb     no       Qip-On     no       Humidity Range     no       Humidity Range     no       Probe Type     no       Auto Switch Off     no       Huf Function     no       HACCP Compliant     no       Marranty     1 Vear       Calendar     no       Pow Point     no       Water Resistant     no       Vater proof     yes       Vater proof     yes       Protective Case     no       Protective Case     no       Protective Case     no       Qual Display     no       Humidity     no	Decid	
TemperatureyesTemperature SensornoWet BulbnoUre DunoClip-OnnoHunidity RangenoProbe TypenoAuto Switch OffnoHold FunctionnoHold FunctionnoHold FunctionnoMin/Max ReadingsyesClendarnoCalendarnoGuerbortnoGuerbortnoVater ResistantnoWater ResistantnoSolar LightyesProber TypenoMater ProofnoProber TypenoMater ResistantnoProber TypenoProber Type	Brand	TFA Dostmann
Temperature SensornoWet BulbnoClip-OnnoHumidity RangenoProbe TypenoAuto Switch OffnoHudf FunctionnoHACP CompliantnoMarranty1YearCalendarnoCalibrationnoDew PointnoWater ResistantnoWater ResistantnoSolar LightyesProbe TypenoMater ResistantnoProbe TypenoMater ResistantnoProbe TypenoProbe TypenoProbe TypenoMater ResistantnoProbe TypenoProbe Typeno	Humidity	no
Wet BulbnoClip-OnnoHumidity RangenoProbe TypenoAuto Switch OffnoHuld FunctionnoHACP CompliantnoMin/Max ReadingsyesVarranty1 VarrCalendarnoPow PointnoWet ResistantnoWater proofnoVater proofnoSolar LightnoProbe TemperaturenoHould FunctionnoSolar LightnoProbe TemperaturenoHundheldnoNonoSolar LightnoProbe TemperaturenoMuthel CalendarnoSolar LightnoProbe TemperaturenoMuthel CalendarnoSolar LightnoProbe TemperaturenoMuthel CalendarnoSolar LightnoSolar Lightno </td <td>Temperature</td> <td>yes</td>	Temperature	yes
ClipOnnoHumidity RangenoProbe TypenoAuto Switch OffnoHold FunctionnoHold FunctionnoMACPC CompliantyesMarranty1 YearCalendarnoAuto Svitch OffnoDew PointnoWater ResistantnoVater ResistantnoSolar LightyesProtective CasenoProtective Caseno <td< td=""><td>Temperature Sensor</td><td>no</td></td<>	Temperature Sensor	no
Humidity RangenoProbe TypenoAuto Switch OffnoHund FunctionnoHACCP CompliantnoMin/Max ReadingsyesWarranty1 VearCalendarnoCalibrationcola BealbiarticationDew PointnoWatterproofyesWatterproofnoSolar LightnoProtective CasenoProbe TemperaturenoHundheldnoProbe TemperaturenoProbe Temperatu	Wet Bulb	no
Probe TypenoAuto Switch OffnoHold FunctionnoHold FunctionnoHACCP CompliantnoMin/Max ReadingsyesWarranty1 YearCalendarnoCalendarnoPow PointnoWatter ResistantnoVater ResistantnoSolar LightnoProtective CasenoProtective CasenoHondheldnoHondheldnoProtective CasenoPour DisplaynoNonoHondheldnoHondheldnoPour DisplaynoNonoHondheldno <t< td=""><td>Clip-On</td><td>no</td></t<>	Clip-On	no
Auto Switch OffnoHold FunctionnoHACCP CompliantnoMin/Max ReadingsyesWarranty1 YearCalendarnoCalendaronCalibrationCan Be CalibratedDew PointnoWater ResistantnoYolder LightyesSolar LightyesProtective CasenoHandheldnoDual DisplaynoSolar LightnoSolar LightnoHandheldno <td>Humidity Range</td> <td>no</td>	Humidity Range	no
Hold FunctionnoHACCP CompliantnoMin/Max ReadingsyesWaranty1 VaraCalendarnoCalendarnoCalibrationCan Be CalibratedDew PointnoWatenproofyesVater ResistantnoSolar LightyesProbect TemperaturenoProbect TemperaturenoHandheldnoCalibrationnoSolar LightnoProbect TemperaturenoFuel TemperaturenoCalibrationnoSolar LightnoHandheldnoCalendarinoSolar LightnoSolar Lightno <td>Probe Type</td> <td>no</td>	Probe Type	no
HACCP CompliantnoMin/Max ReadingsyesWarnanty1 VearCalendarnoCalibrationCan Be CalibratedDew PointnoWatterproofyesWater ResistantnoSolar LightyesProbet TognoProbet TognoProbe	Auto Switch Off	no
Min/Max ReadingsyesWarranty1 VearCalendarnoCalendarCalendarDaw PointOnWatherproofyesWater ResistantnoSolar LightyesProtective CasenoHandheldnoDau PointnoStar LightnoProtective CasenoMatherproofnoStar LightnoHandheldnoStar LightnoStar Light<	Hold Function	no
Warranty1 YearCalendarnoCalibrationCan Be CalibratedDew PointnoWatherproofyeaWater ResistantnoVaterproofnoSolar LightyeaProtective CasenoHandheldnoDual DisplaynoSolar LightnoMater PointnoMater Point<	HACCP Compliant	no
YCalendarnoCalibrationCan Be CalibratedDew PointnoWeatherproofyesWater ResistantnoVolar LightyesSolar LightyesProtective CasenoHandheldnoDual DisplaynoAuter DebnoSolar LightnoRote CasenoMater DebnoMater Debno<	Min/Max Readings	yes
CalibrationCan Be CalibratedDew PointnoWeatherproofyesWater ResistantnoWaterproofnoSolar LightyesProtective CasenoHandheldnoDual DisplaynoCabled ProbenoCabled ProbenoNonoCabled ProbenoNonoCabled ProbenoNonoCabled ProbenoNonoCabled ProbenoNonoCabled ProbenoNonoCabled ProbenoNonoCabled ProbenoNonoCabled ProbenoNono <td< td=""><td>Warranty</td><td>1 Year</td></td<>	Warranty	1 Year
Dew PointnoWeatherproofyesWater ResistantnoWaterproofnoSolar LightyesProtective CasenoHandheldnoDual DisplaynoCabled Probeno	Calendar	no
WeatherproofyesWater ResistantnoWaterproofnoSolar LightyesProtective CasenoProbe TemperaturenoHandheldnoDual DisplaynoCabled Probeno	Calibration	Can Be Calibrated
Water ResistantnoWaterproofnoSolar LightyesProtective CasenoProbe TemperaturenoHandheldnoDual DisplaynoCabled Probeno	Dew Point	no
WaterproofnoSolar LightyesProtective CasenoProbe TemperaturenoHandheldnoDual DisplaynoCabled Probeno	Weatherproof	yes
Solar LightyesProtective CasenoProbe TemperaturenoHandheldnoDual DisplaynoCabled Probeno	Water Resistant	no
Protective CasenoProbe TemperaturenoHandheldnoDual DisplaynoCabled Probeno	Waterproof	no
Probe TemperaturenoHandheldnoDual DisplaynoCabled Probeno	Solar Light	yes
HandheldnoDual DisplaynoCabled Probeno	Protective Case	no
Dual Display no   Cabled Probe no	Probe Temperature	no
Cabled Probe no	Handheld	no
	Dual Display	no
Temperature Resolution +/- 1°C	Cabled Probe	no
	Temperature Resolution	+/- 1°C

Humidity Sensor	no
Comfort Level Indicator	no
Moon Phase	no
Backlight	yes
Indoor Temperature	no
Indoor Humidity	no
Clock	Manual
Transmission Range	no
Transmission Frequency	no
Temperature Range	-25 to 70°C
Temperature Accuracy	+/- 1°C
Measuring Units	°C
Humidity Resolution	no
Humidity Accuracy	no
Power	Battery
IP Rating	IP44
Outdoor Temperature	no
Size : Depth	2.8cm
PC Connection	no
Touch Screen	no
Min/Max Reset	yes
Dew Point Alarm	no
High/Low Humidity Alarm	no
High/Low Temp Alarm	yes
Outdoor Humidity	no
Size : Height	13cm
Size : Width	12.2cm

# **Additional Options**

Temperature Calibration Certificate	2 Point Temperature Calibration (0°C / 60°C)
	2 Point Temperature Calibration (please specify temperature points)
	1 Point Temperature Calibration (0°C)